



805 PATIO STORM DOOR OPERATING INSTRUCTIONS

To open for ventilation when operating insert is in the fully closed position:

- 1.) Place your fingers on the pull handle rail and thumb on the other side of the pull handle.
- 2.) Slide the door sash out of the sash pocket. Using a continuous motion slide operating sash sideways using your fingers on the pull handle.
- 3.) Continue sliding to desired ventilation position.

CAUTION: Always use the pull handle to open and close the operating door insert.

To remove glass insert and screen:

It is easiest to remove the patio storm door inserts to the exterior. To remove to the exterior do the following:

- 1.) Remove the aluminum sill cover by, prying the sill cover up with a regular screwdriver. For best results start next to the meeting rail.
- 2.) Once the sill cover is removed slide the exterior sash to the center of the door. Lift the sash into the upper sash pocket, so it clears the sill track.
- 3.) Bring the bottom of the sash towards you past the sill and remove from the opening. Set aside.
- 4.) Repeat the process for the interior sash

To re-install storm door inserts:

- 1.) Reverse the procedures for removing the storm door inserts starting at the inside and working out.
- 2.) Make sure both storm sash are pushed fully into the sash pockets and the meeting rail has interlocked when you close the door.
- 3.) Use your hand or a rubber mallet to tap the sill cover back into place.

If you need assistance, please call us at **(800) 544-3646**.