



Standard Features and Benefits

Completely Assembled Wooden Frame

- Clear pine that is free of defects
- Preservative treated for protection against elements

Butt-Joint Frame Corners

- Prevents pivoting at corners
- Assembled with screws for weather tight fit.

Hollow Subsill

- Convenient for installing electrical outlets
- Effective housing for heating ducts.

Effective Sloped Sill Design

- Forces water to drain to outside
- Reduces dust and dirt from collecting on sill

Available in Standard Stock Sizes

- Simplified planning and layout
- Readily available for installation

Simple "Building Block" Installation

- Units fit side-by-side for uniform appearance
- Quickly encloses open wall of any length

Unique 3-Lite Design

- 30% more ventilation area than 2-lite windows
- Floor to ceiling view provides "outdoor feeling"

Special Three-Way Ventilation System

- Offers three independently operated glass sash
- Provides wide variety of ventilation settings

Zinc-Alloy Sash Tracks

- Self lubrication for easy operation of sash
- Helps eliminate penetration of water and unwanted drafts

Durable, Full Length, One-Piece Fiberglass Screen Cloth

- Will not rot or discolor
- Will not bend or crease like metal screen
- Effectively keeps out annoying and unwanted insects

Prime T6 Tempered Extruded Aluminum Inserts

- Uniformity and consistency in strength and finishing
- More than 45% stronger than typical T5 aluminum
- Will not break, crack or warp like vinyl extrusions
- Allows for narrower sight lines for better view

Extruded T-6 Screen Frame

- Will not easily bend or twist like rolled aluminum
- Holds screen spline tight to prevent sagging

Optional One-Piece Full Length Storm Panel

- Conveniently fits into screen stop for secure fit
- Provides dual glazing for additional warmth
- Removes easily to outside for cleaning or storage

Permanent Anodized Finish on Inserts

- Penetrated into aluminum for a lasting finish
- Does not discolor or darken like ordinary mill finish
- Smoother surface for less friction, easier operation

Self-Storing Glass Inserts

- Provides ventilation when you desire
- Removable to the inside for easier cleaning

Stainless Steel, Spring Loaded Pin-Locks

- Safely and securely holds sash when open
- Will not break like plastic or weaker metal devices
- Surer grip and full length lift bar for easy handling

Clear 1/8" (DSB) Tempered Safety Glass

- Reduces risk of injury in event of accidental breakage
- Stronger than single strength (SSB) glass

Wrap-Around Glazing

- Provides continuous cushion to help protect glass
- Spline will not shrink at corners like 'set-in' glazing
- Helps reduce accidental glass breakage

Reinforced, Stainless Steel Corner Keys

- Prevents insert corners from easily separating
- Can be removed to replace broken glass

Tempered Steel Tension Spring

- Allows glass sash to easily remove to inside
- Provides for smooth operation of sash

Heavy Duty Meeting Rails With Full Weatherstripping

- Pressure treated felt weatherstripping help prevents water leakage and unwanted drafts
- Full length lift bar for easier operation

Full Ten Year Limited Product Warranty

- Ten (10) year warranty in writing
- Non-prorated — for full ten year period
- Warranty automatically transfers to new owner